

HDMI Audio/Video Distribution Amplifier

Part #HD-12C



What does it do?

Allows the user to broadcast into two screens simultaneously. This distribution amplifier provides high bandwidth to maintain video integrity up to 1080p.

HDMI 1080p 2Ports



1x2 2Port HD-12C Compact D/A

It has compact design, 20inch built-in cable, built-in signal booster to deliver crisp images, extends signal up to 15 meters, and power-free.

Specifications

HD-12C	0 37229 00487 8
HDMI Input Connector	1
HDMI Output Connectors	2
Signal Type	720p, 1080i, 1080p
Video Bandwidth	225MHz
Max. Distance	15m (49ft) Max.
HDCP/DDC Support	Yes
Deep Color Support	Up to 36bit
TMDS Input Voltage	0.5-1.0v (peak-to-peak)
DDC Input Voltage	5v (peak-to-peak)
Power Supply	5v 2A DC (Optional)
Operating Temperature	32°F to 158°F
Standard	HDMI 1.3b
Warranty	One Year

Features:

- Ideal for projectors, presentations & show rooms
- Provides 225MHz bandwidth for video clarity
- Connects multiple video screens from one HD source
- LPCM, DTS-HD & Dolby TrueHD digital audio
- Supports 720p, 1080i & 1080p
- FCC, CE & RoHS

QVS® **The Connectivity Specialists**

West (1-800-344-3371)
2731 Crimson Canyon Drive
Las Vegas, NV 89128

East (1-800-622-9606)
30727 Beverly Road
Romulus, MI 48174

visit us on the web at www.QVS.com

All names & trademarks are property of their respective companies.
All information is subject to change without notice.